

Model No.

TM SERIES

TM SERIES

TM SPECIFICATIONS

MODEL NO.	SECTIONS	SIZES	MAXIMUM HEIGHT	MINIMUM HEIGHT	WINCH SYSTEM	POWER REQUIREMENTS	VERTICAL DEAD LOAD MAX.	WEIGHT IN LBS
TM 358C	3	TOP -2 7/8" BOTTOM -6 5/8"	58'	22'	40:1 1/2 HP	110 VOLTS	950 LBS	1000 LBS
TM 370C	3	TOP - 4 1/2" BOTTOM -8 5/8"	70'	25'	40:1 1 HP	220 VOLTS	950 LBS	2000 LBS
TM 370HDC	3	TOP -6 5/8" BOTTOM -10 3/4"	70'	25'	50:1 1 HP	220 VOLTS	950 LBS	2500 LBS
TM 490C	4	TOP - 4 1/2" BOTTOM -10 3/4"	90'	25'	50:1 1 1/2 HP	220 VOLTS	950 LBS	3550 LBS
*TM 5100RC	5	TOP -2 7/8" BOTTOM -10 3/4"	100'	29'- 6"	50:1 1 1/2 HP	220 VOLTS	700 LBS	3820 LBS

TM SERIES TOWER INFORMATION

The aerodynamic design of the slender, tubular TM Tower makes it more aesthetic capable of supporting large antennae loads. Tubular sections used in the TM towers provide a low wind resistance design. The telescopic cabling extends each section uniformly. Aircraft grade galvanized cable of 7 x 19 construction is used on all models. The TM Tower is free standing, without the aid of bracket or guys.

All TM towers include a hinged base mount that is installed in concrete. This base mount allows the tower to be hinged at ground level and tilted into a vertical position.

The TM towers are hot-dipped galvanized finish after fabrication for maintenance free finish.

The top section of each tower model is adapted to accept an accessory rotator cage assembly. If a rotator assembly is not desired, then a mast adapter can be ordered as an accessory item. All standard mast adapters accommodate a two (2) inch O.D. mast size.

ACCESSORIES:

CO-3 for TM
Tilting Gin Pole
Cable Kit
TB-2 Trust Bearing
Remote Control Kit
Motor Control Assembly
Rotator Cage Assembly
Work Platform

MODEL NO.	PRICE	70 MPH WIND ALLOWABLE SAIL AREA
TM 358	\$5,995.00	15 SQ.FT.
TM 370	\$11,499.00	15 SQ.FT.
TM 370HD	\$12,899.00	35 SQ.FT.
TM 490	\$14,100	20 SQ.FT.
*TM 5100R	\$16,200	20 SQ.FT.